

PE Protective Film is a type of PE film used for coating glue. The usual colors are clear, white, blue and black and white. Our equipment has online thickness measurement, the production of films with better thickness uniformity. We can customize different types of PE film according to customer requirements, such as high temperature resistance, high strength and so on.

Particulars:

| Particulars | Test Method | Unit | Values |
|--------------------------------|---|-------------------|----------------|
| Width | Measuring Tape | mm | Up to 3000 |
| Thickness | | microns | 15 - 200 |
| Tensile Strength | GB/T 1040.3-2006 | MD (Mpa) | 15 to 50 |
| | | TD (Mpa) | 15 to 50 |
| Elongation at Break | GB/T 1040.3-2006 | MD (%) | 180 to 1300 |
| | | TD (%) | 180 to 1300 |
| Density | | g/cm ³ | 0.925-1.000 |
| Treatment value | ASTM D-2578 | Dynes/ cm | 44 |
| Coefficient of Friction | GB/T 10006-1988 | | 0.10 - 0.60 |
| Winding Direction | | | Treated Inside |
| Roll Diameter | | Meters | 500 - 10000 |
| Core inner diameter | | mm | 76 |
| Type of Core | Paper Core/ Plastic Core | | |
| Film Color | Clear, White, Blue, Green, Black and white and etc. | | |

1. We can offer outside treated on request.
2. Packaging - Individually wrapped in plastic thin wrapping film.
3. Palletized packing available on request.



Features:

1. Can be customized.
2. A variety of colors, like white, blue, green, black and white.
3. Good thickness uniformity.
4. The color will not migrate to the tape.
5. Can be printed LOGO.

Terms and Conditions:

| | |
|----------------------------------|--|
| Storage Condition | The film should be stored safely at ambient temperature, Dry atmosphere and away from direct sunlight |
| Shelf Life | The total shelf life of this film is 6 months from the date of manufacturing |
| Terms of Usage | <p>Data provided here is proprietary to Kaide Material , and Kaide Material reserves the right to make any changes to the information in this document or to any products and services at any time without notice.</p> <p>The product information is based on our present knowledge and is intended to provide the information on our current products and how they might be used in a general term. It is the Users' responsibility to independently determine suitability of any products and to test and verify the same for their individual usage. Kaide Material makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Kaide Material assume</p> |
| Elimination of film waste | Film is Recyclable. |

