

PE Self-release Film is used for the VHB tape. The PE film is made of special formula, doesn't need to be coated silicon. The color of the film can be customized. And the main colors are red and orange. Also the film can be printed LOGO. The colors of the PE film will not migrate to the VHB tape.

Particulars:

Particulars	Test Method	Unit	Values
Width	Measuring Tape	mm	Up to 2000
Thickness		microns	15 - 200
Release force	FTM 10,TESA7475	One side(g/inch)	600-1000
		Another(g/inch)	1000-1400
Tensile Strength	GB/T 1040.3-2006	MD (Mpa)	15 to 50
		TD (Mpa)	15 to 50
Elongation at Break	GB/T 1040.3-2006	MD (%)	180 to 1300
		TD (%)	180 to 1300
Density		g/cm3	0.925-1.000
Coefficient of Friction	GB/T 10006-1988		0.10 - 0.60
Winding Direction			Treated Inside
Roll Diameter		Meters	500 - 10000
Core inner diameter		mm	76
Type of Core	Paper Core/ Plastic Core		
Film Color	Transparent,White,Blue,Green,Red,Yellow, Orange and etc.		

1.Packaging - Individually wrapped in plastic thin wrapping film

- 2. Rolls are supplied in soft packing.
- 3. Palletized packing available on request.





Features:

- 1. Can be customized.
- 2. A variety of colors, like red, blue, green, white, yellow, orange.
- 3. Good thickness uniformity.
- 4. The color will not migrate to the tape.
- 5. Can be printed LOGO
- 6. The usual thickness is 120um.

Terms and Conditions:

Storage	The film should be stored safely at ambient temperature, Dry	
Condition	atmosphere and away from direct sunlight	
Shelf Life	The total shelf life of this film is 6 months from the date of manufacturing	
Terms of Usage	Data provided here is proprietary to Kaide Material , and Kaide Material reserves the right to make any changes to the information in this document or to any products and services at any time without notice. The product information is based on our present knowledge and is intended to provide the information on our current products and how they might be used in a general term. It is the Users' responsibility to independently determine suitability of any products and to test and verify the same for their individual usage. Kaide Material makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Kaide Material assume	
Elimination of film waste	Film is Recyclable.	

